

AMENDMENTS TO THE CLAIMS:

The listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claims 1-7 (Canceled)

8. (Original) Cattle stanchion apparatus for controlling movement of cattle

relative to such apparatus, said cattle stanchion apparatus comprising:

a fixed support structure;

a plurality of pairs of release stanchion bar assemblies supported by the

fixed support structure along the length of the fixed structure;

(each pair of release stanchion bar assemblies including a pair of facing

double release stanchion bars pivotally connected at their intermediate portions for

swinging movement towards and away from one another when engaged by a cow;

the space between each pair of stanchion release bars defining a cattle head

receiving opening;

a latch bracket on the upper portion of each stanchion release bar formed with a latch pin;

latch heads on the fixed structure, each disposed above the mid-section of each of the release stanchion bar assemblies;


release bar or assembly?

a pair of flaps pivotally supported by each latch head, each of the flaps being formed with a locking slot; and

a positioner rod horizontally rotatably carried by the fixed support structure and having flap lifting studs arranged engageable with the flaps to raise and lower the flaps whereby *each latch pin of a respective* ~~(the latch pins of the stanchion release bars)~~ ^{is} ~~are~~ movable into and out of engagement with ~~the~~ ^{respective} ~~lock slots~~ to control the swinging movement of the stanchion release bars.

9. (Original) Cattle stanchion apparatus as set forth in Claim 8, wherein the release stanchion bars are biased to automatically assume a position in which the upper ends of such stanchion bars are spaced apart.

10. (Original) Cattle stanchion apparatus as set forth in Claim 8, wherein the lower portion of the release stanchion bars are weighted to cause such release stanchion bars to automatically assume a position wherein their upper ends are spaced apart.


 119/749,750

11. (Original) Cattle stanchion apparatus as set forth in Claim 8, wherein a flap can be manually moved into disengagement with its respective latch head whereby the latch head's release stanchion bar is manually moveable to an open downed cow releasing position:

-- each said or one of said flaps

said or the
^

latch heads on the fixed structure, each disposed above the mid-section of each of the release stanchion bar assemblies;

 latch heads on fixed structures

a pair of flaps pivotally supported by each latch head, each of the flaps being formed with a locking slot; and

a positioner rod horizontally carried by the fixed support structure and having flap lifting studs arranged engageable with the flaps to raise and lower the flaps

so see claim 8

whereby the latch pins of the stanchion release bar are movable into and out of

engagement with the lock slots to control the swinging movement of the release stanchion bars, with the release stanchion bars being locked in a vertically extending position when the latch pins are engaged with the lock slots and being free to undergo swinging movement when the latch pins are out of engagement with the slots.

see claim 8

12. (Original) Cattle stanchion apparatus for controlling movement of cattle

relative to such apparatus, said cattle stanchion apparatus comprising:

a fixed support structure;

a plurality of release stanchion bar assemblies supported by the fixed structure along the length of the fixed structure;

each pair of release stanchion bar assemblies including a pair of facing double release stanchion bars pivotally connected at their intermediate portions for simultaneous swinging movement towards and away from one another;

the space between each pair of stanchion release bars defining a cattle head receiving opening;

a latch bracket on the upper portion of each stanchion release bar formed with a latch pin;

latch heads on the fixed structure, each disposed above the mid-section of each of the release stanchion bar assemblies;

a pair of flaps pivotally supported by each latch head, each of the flaps being formed with a cow training abutment surface and with a locking slot; and

a positioner rod horizontally rotatably carried by the fixed structure and having flap lifting studs arranged engageable with the flaps to raise and lower the flaps whereby the latch pins of the stanchion release bar are movable into and out of engagement with the abutment surface, with the locking slots to control the swinging movement of the stanchion release bars, and with the stanchion release bars being locked in a vertical position when the latch pins are engaged with the lock slot and locked against swinging movement towards one another when the latch pins are engaged with the cow training abutment surfaces.

13. (Original) Cattle stanchion apparatus as set forth in Claim 12, wherein the release stanchion bars are biased to automatically assume a position in which the upper ends of such stanchion bars are spaced apart.

14. (Original) Cattle stanchion apparatus as set forth in Claim 12, wherein the lower portion of the release stanchion bars are weighted to cause such stanchion bars to automatically assume a position wherein their upper ends are spaced apart.

15. (Original) Cattle stanchion apparatus as set forth in Claim 8, wherein each flap additionally includes an elongated aperture that receives a lifting stud.

16. (Original) Cattle stanchion apparatus as set forth in Claim 9, wherein each flap additionally includes an elongated temperature compensating aperture that receives a lifting stud.

17. (Original) Cattle stanchion apparatus as set forth in Claim 10, wherein each flap additionally includes an elongated temperature compensating aperture that receives a lifting stud.

18. (Original) Cattle stanchion apparatus as set forth in Claim 12, wherein each flap additionally includes an elongated temperature compensating aperture that receives a lifting stud.

19. (Original) Cattle stanchion apparatus as set forth in Claim 13, wherein each flap additionally includes an elongated temperature compensating aperture that receives a lifting stud.

20. (Original) Cattle stanchion apparatus as set forth in Claim 14, wherein each flap additionally includes an elongated temperature compensating aperture that receives a lifting stud.